

P.C.B Layout(top view)


主要技术特性:

1. 额定电负荷: 30V, 0.5A;
2. 接触电阻: $\leq 0.03\Omega$;
3. 绝缘电阻: $\geq 100\Omega$;
4. 耐压: AC500V(50HZ) 1min;
5. 插拔力: 3-20N;
6. 寿命: 5,000次。

主要技术要求

1. 未注线性公差:
0.0-10.0mm $\pm 0.10\text{mm}$
10.0-20.0mm $\pm 0.15\text{mm}$
20.0-50.0mm $\pm 0.20\text{mm}$
2. 外观应良好, 无锈蚀、裂痕、电镀不良等现象。

Model No.	1	2	3	4
PIN ϕ	1.65	2.0	2.35	2.5



序号	名称	数量	材料	镀涂
6	盖子	1	绝缘电木板	
5	底座	1	PBT	(黑)
4	平片	1	H62黄铜带T=0.30	铜锡
3	弯片	1	H62黄铜带T=0.30	锡铈
2	簧片	1	65Mn钢带T=0.25/(磷铜)	锡铈
1	插针 (PIN)	1	H62铜棒	铜锡

DONG GUAN XI BANG ELECTRONIC CO., LTD

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME		DC POWER JACK		DRAWING		G.C.Chen		DWG.No.	
PART NO.				CHECK		G.C.Chen		REV. A	
UNIT :		TOLERANCE		ANGLE		APPROVAL		DATE	
mm		OTHERWISE		0°±3'		SCALE		PAGE	
		UP TO 10 ±0.1				2:1		1 OF 1	
		ABOVE 10- 20 ±0.15							
		ABOVE 20- 50 ±0.2							