


按点示意图
SCHEMATIC



PIN	Φ2.0	Φ2.35	Φ2.5
APPD.			

主要技术特性:

1. 额定电负荷: DC 12V, 1A;
2. 接触电阻: $\leq 30m\Omega$;
3. 绝缘电阻: $\geq 100M\Omega$;
4. 耐压: AC500V(50-60HZ)1min;
5. 插拔力: 2.94-29.4N;
6. 寿命: 5,000次。

主要技术要求

1. 未注线性公差:
 0.0-10.0mm $\pm 0.20mm$
 10.0-20.0mm $\pm 0.25mm$
 20.0-50.0mm $\pm 0.30mm$
2. 外观应良好, 无锈蚀、裂痕、电镀不良等现象。

6	基座	1	PBT	(黑)
5	PIN	1	H59黄铜棒	Ni
4	平片	1	H62黄铜带T=0.4t	银
3	弯片	1	H62黄铜带T=0.4t	银
2	簧片	1	Qsn6.5-0.1	银
1	盖脚	1	H62黄铜带T=0.2t	银
序号	名称	数量	材料	镀涂

DONG GUAN XI BANG ELECTRONIC CO., LTD

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME		DC POWER JACK		DRAWING		Y,C,ZHANG		DWG.No.		SBICL	
PART NO.				CHECK		G.C.Chen		REV.		A1	
UNIT : mm	TOLERANCE OTHERWISE	UP TO 5	± 0.2	ANGLE	APPROVAL	SCALE	2:1	DATE	PAGE	1 OF 1	
		ABOVE 5~30	± 0.3								