



材料:

- A按钮: PA46 (黑色)
- B盖板: 不锈钢301 (清洗)
- C内薄膜: 进口聚酰亚胺(黄色)
- D簧片: 不锈钢 (镀银)
- E基座: LCP (黑色)
- F卡件: 磷铜 (镀银)
- G外薄膜: 进口聚酰亚胺(黄色)

主要技术规格:

1. 额定值: 50mA DC12V
2. 接触电阻: 50mΩ
3. 操作力: 250gf±50gf
4. 行程: 0.3±0.05mm
5. 绝缘电阻: 100MΩ
6. 抗电强度: 250V 50HZ 1Min.
7. 寿命: 5万Cycles

DONG GUAN XI BANG ELECTRONIC CO., LTD

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME		SWITCH		DRAWING		Y.C,ZHANG	DWG.No.	SBICL
PART NO.				CHECK		G.C.Chen	REV.	A1
UNIT : mm	TOLERANCE	UP TO 5	±0.2	ANGLE	APPROVAL	DATE		
	OTHERWISE	ABOVE 5~30	±0.3			SCALE	2:1	PAGE
		ABOVE 30	±0.5					
		ANGLE	±3°					