



材料:

- A桃 心: PA46(黑色)
- B底 座: PA46(黑色)
- C盖 板: 不锈钢301(清洗)
- D接触弹簧: 复银铜(银白色)
- E弹 簧: 不锈钢301(银白色)

主要技术规格:

1. 额 定 值: 10mA DC12V
2. 接触电阻: $\leq 100m\Omega$
3. 操 作 力: $2-100gf \pm 50gf$ $250gf \pm 50gf$
4. 行 程: $0.65 \pm 0.2mm$
5. 绝缘电阻: $\geq 100M\Omega$
6. 耐压强度: AC110V 50Hz/1Min.
7. 寿 命: 1万Cycles Min
8. 温度范围: $-30^{\circ}C$ TO $+80^{\circ}C$

DONG GUAN XI BANG ELECTRONIC CO., LTD

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME		MULTI FUNCTION SWITCH		DRAWING		Y,C,ZHANG		DWG.No.		SBICL	
PART NO.				CHECK		G.C.Chen		REV.		A1	
	UNIT :	TOLERANCE	UP TO 5	±0.2	ANGLE	APPROVAL		DATE			
	mm	OTHERWISE	ABOVE 5~30	±0.3							
			ABOVE 30	±0.5							
			ANGLE	±5'	SCALE	2:1	PAGE	1 OF 1			