



安装尺寸

材料:

- A 底座: 进口增强尼龙 (黑色)
- B 嵌件: 进口磷青铜 (镀银与银白色)
- C 接触弹簧: 进口磷青铜 (镀银与银白色)
- D 盖板: 进口增强尼龙 (整体清洗与黑色)
- E 按钮: 进口增强尼龙 (黑色)
- F 贴片按钮: 不锈钢 (原色)

主要技术规格:

1. 额定值: 0.1A MAX
2. 接触电阻: $\leq 200m\Omega$
3. 操作力: $500gf \pm 30gf$
4. 行程: $1.0 \pm 0.3mm$
5. 绝缘电阻: $\geq 100M\Omega$
6. 耐压强度: AC250V 50HZ/ 1Min.
7. 寿命: 5万Cycles Min
8. 额定电压: DC 12V

DONG GUAN XI BANG ELECTRONIC CO., LTD

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME		DETECTION SWITCH		DRAWING		Y.C.ZHANG		DWG.No.		SBICL	
PART NO.				CHECK		G.C.Chen		REV.		A1	
UNIT :		TOLERANCE		UP TO 5		ANGLE		APPROVAL		DATE	
mm		OTHERWISE		ABOVE 5~30		$0^{\circ} \pm 5'$		SCALE		PAGE	
				± 0.2				2:1		1 OF 1	
				± 0.3							
				± 0.5							
				$\pm 3'$							