


P.C.B LAYOUT
BOTTOM VIEW

注“*”表示关键尺寸(8个)



SCHEMATIC

- 1、开关动作力: 100±30gf.cm
- 2、回返力: 30gf.cm Min
- 3、额定值: DC30V 0.1A
- 4、接触电阻: 200mΩ Max
- 5、绝缘电阻: ≥100MΩ (MinDC250V)
- 6、耐压: 250V AC(50HZ或60HZ)/1min
- 7、机械寿命: 50000 Min

NO.	PARTS	MATERIALS	QTY	FINISH
6	TERMINAL	BRASS	1	Ag PLATED
5	CASE	PA66	1	BLACK
4	SPRING	SUS	1	NATURAL
3	CONTACT	PBS STRIP	1	Ag CLAD
2	BUTTON	PA66	1	YELLOW
1	COVER	PA66	1	BLACK

DONG GUAN XI BANG ELECTRONIC CO., LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		DETECTION SWITCH		DRAWING		Y.C.ZHANG		DWG.No.		SBICL	
PART NO.				CHECK		G.C.Chen		REV.		A1	
UNIT : mm	TOLERANCE	UP TO 5	±0.2	ANGLE	APPROVAL	DATE					
	OTHERWISE	ABOVE 5~30	±0.3			SCALE	2:1	PAGE		1 OF 1	