



| PART NO. | A | B | C |
|-----------|-----|-----|-----|
| BC3P25H54 | 5.4 | 3.8 | 4.6 |
| BC3P25H60 | 6.0 | 4.4 | 5.2 |
| BC3P25H65 | 6.5 | 4.9 | 5.7 |
| BC3P25H70 | 7.0 | 5.4 | 6.2 |
| BC3P25H75 | 7.5 | 5.9 | 6.7 |
| BC3P25H80 | 8.0 | 6.4 | 7.2 |

性能:

额定电流: 2.0A

额定电压: 12V

耐电压: 500V

接触电阻: 30mΩ

绝缘电阻: 500MΩ

工作温度: -40℃~+85℃

塑件(材质): LCP

接触点(材质): 磷铜, 镀金



东莞市溪榜电子有限公司

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

| PART NAME | | CONNECTOR | | | DRAWING | Y,C,ZHANG | DWG.No. | SBICL |
|--------------|------------------------|--------------|------|-------|----------|-----------|---------|------------|
| PART NO. | | | | | CHECK | G.C.Chen | REV. | A1 |
| UNIT : mm | TOLERANCE OTHERWISE | UP TO 5 | ±0.2 | ANGLE | APPROVAL | | DATE | 26-09-2013 |
| | | ABOVE 5 ~ 30 | ±0.3 | | | | SCALE | 2:1 |
| | | ABOVE 30 | ±0.5 | σ±5 | | | | |