



RECOMMENDED P.C.B HOLE LAYOUT
COMPONENT SIDE VIEW(TOLERANCE: +/-0.05)

技术规格:

1:电性能

- 1.1额定电流: 1.8A
- 1.2接触阻抗: 30mΩ MAX
- 1.3绝缘阻抗: 1000MΩ MIN 500V DC
- 1.4耐压测试: 500V AC

2:机械性能

- 2.1插入力: 3.57kgf MAX
- 2.2拔出力: 1.00kgf MIN
- 2.3使用寿命: 5000次
- 2.4耐温性:烤箱测试: 温度260±5℃, 时间5分钟

2.5工作温度: -30℃~+80℃

3:材质及表面处理:

- 3.1胶芯: LCP 黑色 UL94V-0
- 3.2端子: C5191,镍底, 镀金3.0μ"
- 3.3外壳: C2680, 表面镀镍60μ"
- 3.4符合ROHS的要求

PART NAME		CONNECTOR			DRAWING	Y.C.ZHANG	DWG.No.	SBICL
PART NO.		MICRO 5P 四脚平口无柱 6.2MM			CHECK	G.C.Chen	REV.	A1
UNIT :	TOLERANCE OTHERWISE	UP TO 5	±0.2	ANGLE	APPROVAL		DATE	
		ABOVE 5 3D	±0.3		SCALE	2:1	PAGE	1 OF 1
mm		ABOVE 3D	±0.5	∠≤5°				