



- Note:
- Material:
 - Housing: High temperature thermoplastic with g.f,UL94v-0
 - Contact: copper alloy,t=0.20mm
 - Shell: copper alloy,t=0.25mm
 - Specification:
 - Current rating:1.5PIN 1.8A Max/2,3,4PIN 1A Max.
 - Dielectric withstanding voltage: 100 V(ac) for 1 min.
 - Contact resistance: 30 mΩ Max.
 - Insulation resistance: 100 MΩ Min.
 - Total mating force: 3.57 Kgf Max.
 - Total unmating force: 1.0 Kgf Min.
 - Temperature range: -30°C~80°C

A 01 S B X X X X X XX-835
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪

- ① 外壳材质: 1:GS180R-H
- ② 外壳电镀: 1:160u''
2:雾150u''
3:10Au1u''(脚)
4:Au1u''
- ③ 端子电镀: 01:Au1u'';02:Au1.5u'';03:Au3u''
05:Au5u'';10:Au10u'';15:Au15u'';30:Au30u''
- ④ 主体颜色: B:黑色
- ⑤ 主体材质: 1:LCP
- ⑥ 端子材质: 4:CSI91R-EN



COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		CONNECTOR		DRAWING	Y,C,ZHANG	DWG.No.	SBICL
PART NO.		Micro usb 5PB Type 插板7.2有柱脚长1.1四脚全插		CHECK	G.C.Chen	REV.	A1
UNIT : mm	TOLERANCE	UP TO 5	±0.2	APPROVAL	SCALE	DATE	
	OTHERWISE	ABOVE 5~30	±0.3			PAGE	1 OF 1
		ANGLE	±5				