



Note:  
 1.Material:  
 1.1 Housing: High temperature thermoplastic with g.f,UL94v-0  
 1.2 Contact: copper alloy,t=0.20mm  
 1.3 Shell: copper alloy or sus,t=0.25mm  
 2.Specification:  
 2.1 Current rating:1,5PIN 1.8A Max/2,3,4PIN 1A Max.  
 2.2 Dielectric withstanding voltage: 100 V(ac) for 1 min.  
 2.3 Contact resistance: 30 mΩ Max.  
 2.4 Insulation resistance: 100 MΩ Min.  
 2.5 Total mating force: 3.57 Kgf Max.  
 2.6 Total unmating force: 1.0 Kgf Min.  
 2.7 Temperature range: -30°C~80°C

A 01 S B X X X X XX-325  
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪

外壳材质 1:G680R-H  
 7:SU8304R-1/2H  
 外壳电镀 1:N50u''  
 2:雾150u''  
 3:雾Au1u''(脚)  
 4:Au1u''  
 端子电镀 01:Au1u'';02:Au1.5u'';03:Au3u''  
 05:Au5u'';10:Au10u'';15:Au15u'';30:Au30u''  
 主体颜色 B:黑色  
 主体材质 1:L0P  
 端子材质 4:GS191R-BH



COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME	CONNECTOR		DRAWING	Y,C,ZHANG	DWG.No.	SBICL
PART NO.	Micro usb 5s B Type 有焊脚有杜插板式6.4		CHECK	G.C.Chen	REV.	A1
UNIT : mm	TOLERANCE	UP TO 5 ±0.2	APPROVAL	SCALE	DATE	PAGE
	OTHERWISE	ABOVE 5~30 ±0.3 ABOVE 30 ±0.5 ANGLE ±3°				