



Note:  
 1.Material:  
 1.1 Housing: High temperature thermoplastic with g.f,UL94v-0  
 1.2 Contact: copper alloy,t=0.20mm  
 1.3 Shell: copper alloy,t=0.25mm  
 2.Specification:  
 2.1 Current rating:1,5PIN 1.8A Max/2,3,4PIN 1A Max.  
 2.2 Dielectric withstanding voltage: 100 V(ac) for 1 min.  
 2.3 Contact resistance: 30 mΩ Max.  
 2.4 Insulation resistance: 100 MΩ Min.  
 2.5 Total mating force: 3.57 Kgf Max.  
 2.6 Total unmating force: 1.0 Kgf Min.  
 2.7 Temperature range: -30°C~80°C

A 01 S B X X X X XX-382  
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪

外壳材质 1: C268RH  
 外壳电镀 1: Ni5u''  
 2: 雾150u''  
 3: NiAu1u'' (黑)  
 4: Au1u''  
 端子电镀 01: Au1u'' ;02: Au1.5u'' ;03: Au3u''  
 05: Au5u'' ; 10: Au10u'' ;15: Au15u'' ;30: Au30u''  
 主体颜色 B: 黑色  
 主体材质 1: LCP  
 端子材质 4: CS19RH-EH



COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		CONNECTOR		DRAWING	Y,C,ZHANG	DWG.No.	SBICL
PART NO.		Micro usb 5PB Type 插板7.2无柱脚长1.1四脚全插		CHECK	G.C.Chen	REV.	A1
UNIT : mm	TOLERANCE	UP TO 5	±0.2	APPROVAL		DATE	
	OTHERWISE	ABOVE 5~30	±0.3	SCALE	2:1	PAGE	1 OF 1
		ABOVE 30	±0.5				
		ANGLE	±5				
		ANGLE	0°±5'				