



PCB图仅供参考
RECOMMEND PCB LAYOUT

- Note:
- Material:
 - Housing: LCP High temperature thermoplastic with g.f,UL94v-0
 - Contact: copper alloy,t=0.15mm
 - Shell: SUS304,t=0.30mm
 - Specification:
 - Current rating:1.5PIN 1.8A Max/2,3,4PIN 1A Max.
 - Dielectric withstanding voltage: 100 V(ac) for 1 min.
 - Contact resistance: 30 mΩ Max.
 - Insulation resistance: 100 MΩ Min.
 - Total mating force: 3.57 Kgf Max.
 - Total unmating force: 1.0 Kgf Min.
 - Temperature range: -30°C~80°C

A 01 S B X X X X X XX-283
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪

外壳材质 7: SUS304R-1/2H
外壳电镀
1: Ni50u"
2: 雾T50u"
3: NiAu10u" (脚)
4: Au1u"

端子电镀 01: Au1u"; 02: Au1.5u"; 03: Au3u"
05: Au5u"; 10: Au10u"; 15: Au15u"; 30: Au30u"

主体颜色 B: 黑色
主体材质 1: LCP
端子材质 4: CS19 IR-EN



COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME		CONNECTOR		DRAWING	Y,C,ZHANG	DWG.No.	SBICL
PART NO.		MICRO USB IS B TYPE牛角型全插6.60有柱加长0.75无导位		CHECK	G.C.Chen	REV.	A1
UNIT : mm	TOLERANCE	UP TO 5	±0.2	APPROVAL		DATE	
	OTHERWISE	ABOVE 5 ~ 30	±0.3	SCALE	2:1	PAGE	1 OF 1
		ABOVE 30	±0.5				
		ANGLE	±5				