



备注:

1.材质:

1.1胶芯: LCP+30%G.F

1.2端子: C7025, T=0.15mm; 镍底, 镀金

1.3外壳: 不锈钢, T=0.17mm; 表面镀镍

1.4卡钩: 不锈钢, T=0.30mm; 表面镀镍

1.5弹片: 不锈钢, T=0.10mm

2.主要特性:

2.1额定电流: 0.5A

2.2接触阻抗: 40mΩ MAX

2.3绝缘阻抗: 100MΩ MIN 250V DC

2.4耐压测试: 100V AC

2.5沾锡性: 温度245±5℃

2.6整体插入力: 2.0kgf MAX

耐久前整体拔出力: 0.8kgf MIN

耐久后整体拔出力: 0.6kgf MIN

2.7使用寿命: 10000次

2.8工作温度: -25℃~+80℃



东莞市溪榜电子有限公司

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME	CONNECTOR			DRAWING	Y,C,ZHANG	DWG.No.	SBICL
PART NO.	TYPE-C/M SMT 铆合式鱼叉脚厚3.0			CHECK	G.C.Chen	REV.	A1
UNIT : mm	TOLERANCE	UP TO 5	±0.2	APPROVAL		DATE	
	OTHERWISE	ABOVE 5~30	±0.3				
		ABOVE 30	±0.5	SCALE	2:1	PAGE	1 OF 1
		ANGLE	±3°				