



SPECIFICATION

Contact Rating: 50mA, 12V DC
 Contact Resistance: 100mΩ max
 Insulation Resistance: 100mΩ min. 500V DC
 Dielectric Strength: 250V AC/1minute
 Travel: 0.25mm
 Operating Temp: -40°C~+90°C
 Storage Temp: -30°C~+80°C

PAPT NO	TC-111A-X
Operating Force	A:130gf B:200gf C:300gf D:500gf
Height	H:6.65



P.C.B Mounting hole dimensionis



It is suggested to use P,C,B Boarol of 1.6mm thick

ITEM	PAPT NAM	FTER,NC	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	—	2	Brass (0.30t)	Plating silvering	—
④	Contact	—	1	F.ag/SUS	Natural	—
③	Base	—	1	Pa46	—	—
②	Cover	—	1	Brass	Plating Nickel	—
①	Keystake	—	1	Steel ball	—	—

DSND		DATE		SCALE: N/A	MODEL TYPE: TACT SWITCH
DWN		DATE		VIEW:	PART NO.:
CHKD		DATE		UNIT: mm/in	DWG NO TC-111A-X
APPD		DATE		SIZE: A4	WEIGHT 1.0g
UNSPECIFIED TOLERANCES					SHEET 1/1
DONG GUAN XI BANG ELECTRONIC CO., LTD					REVISION A0

MARK	DESCRIPTION	DATE	REVISED	APPROVED	units: mm
ΔX					tolerance: X.X ±0.2mm
ΔX					X.XX ±0.1mm
ΔX					X.XXX ±0.05mm
REVISIONS					