



SPECIFICATION
 Contact Rating: 50mA, 12V DC
 Contact Resistance: 100mΩ max
 Insulation Resistance: 100mΩ min.500V DC
 Dielectric Strength: 250V AC/1minute
 Travel: 0.35mm
 Operating Temp: -40 ~ +90
 Storage Temp: -30 ~ +80

PAPT NO	TC-1110-X
Operating Force	A:130gf B: 200gf C:300gf D:500gf
Height	H:6.65

⑤	Terminal	—	4	Brass (0.30t)	Plating silvering	—
④	Contact	—	1	F.ag/Sus	Natural	—
③	Base	—	1	PPA	—	—
②	Cover	—	1	Brass	Plating Nickel	—
①	Keystake	—	1	Steel ball	—	—
ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK

					units: mm	DSND	DATE	SCALE: N/A	MODEL TYPE: TACT SWITCH		
					tolerance: X.X ±0.2mm	DWN	DATE	VIEW:	PART NO.:		
					X.XX ±0.1mm	CHKD	DATE	UNIT: mm/in	DWG NO		
					X.XXX ±0.05mm	APPD	DATE	SIZE: A4	TC-1110-X		
REVISIONS					UNSPECIFIED TOLERANCES	DONG GUAN XI BANG ELECTRONIC CO., LTD			WEIGHT 1.0g	SHEET 1/1	REVISION A0
www.alpsr.com www.gdxdz.com www.xbswitch.com											