


Code-x	H	Code-x	H
A	4.3	O	11.0
B	4.5	P	11.5
C	5.0	Q	12
D	5.5	R	12.5
E	6.0	S	13.0
F	6.5	T	13.5
G	7.0	U	14.0
H	7.5	V	15.0
I	8.0	W	15.5
J	8.5	X	16
K	9.0	Y	16.5
L	9.5	Z	17
M	10.0	18	18
N	10.5	19	19


SPECIFICATION
 Contact Rating: 50mA 12V DC
 Contact Resistance: 100mΩ max
 Insulation Resistance: 100MΩ min.500V DC
 Dielectric Strength: 250V AC/1minute
 Travel: 0.25mm
 Operating Temp: -20°C~+70°C
 Storage Temp: -40°C~+85°C

PACKING REEL TYPE

CIRCUIT DIAGRAM



P.C.B MOUNTING HOLES



PAPT NO	TS-1102S-X-X-X
Operating Force	A:100gf B:160gf C:260gf
Height	Code-x
Color	B:Black BR:Brown R:Red O:Orange Y:Yellow BL:Blue W:White

⑤ Terminal	4	Brass (0.30t)	Plating silvering	-----		
④ Contact	1	Fag/Sus	Natural	-----		
③ Base	1	Pa46	-----	-----		
② Cover	1	Spcc	Plating Nickel	-----		
① Keystake	1	Pa46	-----	-----		
ITEM	PAPT NAMP	TER.NO	QTY	MATERIAL	FINISHING	REMARK

REVISIONS						UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE: TACT SWITCH		
ΔX						units: mm	DWN	DATE	VIEW:	PART NO.:		
ΔX						tolerance:	CHKD	DATE	UNIT: mm/in	DWG NO		
ΔX						X.X ±0.2mm	APPD	DATE	SIZE: A4	TS-1102S-X-X-X		
ΔX						X.XX ±0.1mm						
MARK	DESCRIPTION	DATE	REVISED	APPROVED	X.XXX ±0.05mm							
www.alpsr.com www.gdxjdz.com www.xbswitch.com							DONG GUAN XI BANG ELECTRONIC CO., LTD			WEIGHT 1.0g	SHEET 1/1	REVISION A0