

PCB WELDING DRAWING

The Main Thchnology Performance

主要技术性能

Rate vltage.current:50mA DC 12V

额定电压.电流: 50mA DC 12V

Contact resistance:≤100mΩ

接触电阻: ≤100mΩ

Operating force: 260±50gf

操作力: 260±50gf

Travel: 0.20±0.1mm

行程: 0.20±0.1mm

Insulated resistance: ≥100mΩ


绝缘电阻: ≥100mΩ

Dielectric strength: ≥250VAC/lmin

绝缘电强度: ≥250VAC/lmin

Endurance: ≥30000

耐力: ≥30000



CIRCUIT DIAGRAM

D	Yellow membrane	polyimide	1	Orange
C	Shrapnel	SUS	2	plate with silver
B	Clasp	phosphorous copper	1	plate with solver
A	Pedestal	LCP	1	grey
ITEM	DESCRIPTION	MATERIAL	QTY	FINSH/COLOR

DSND		DATE		SCALE: N/A	MODEL TYPE: TACT SWITCH
DWN		DATE		VIEW:	PART NO.:
CHKD		DATE		UNIT: mm/in	DWG NO
APPD		DATE		SIZE: A4	TS-1177A-C
				DONG GUAN XI BANG ELECTRONIC CO., LTD	WEIGHT 1.0g
					SHEET 1/1
					REVISION A0

MARK	DESCRIPTION	DATE	REVISED	APPROVED	units: mm
ΔX					tolerance:
ΔX					X.X ±0.2mm
ΔX					X.XX ±0.1mm
MARK					X.XXX ±0.05mm
REVISIONS					UNSPECIFIED TOLERANCES
www.alpsr.com www.gdxdz.com www.xbswitch.com					