




A:With B:without



SPECIFICATION

Contact Rating 50mA, 12V DC
Contact Resistance 100mΩ max.
Insulation Resistance 100MΩ min. 500V DC
Dielectric Strength 250V AC/1 minute
Travel 0.25mm
Operating Temp. -25°C ~ +70°C
Storage Temp. -30°C ~ +80°C
Force Touch 250 ± 100

PAPT NO	TS-1183SA-X-X
Operating Force	A:100gf B:160gf C:260gf
Fixed column	A:With B:without

ITEM	PAPT NAMF	TER.NO	QTY	MATERIAL	FINISHING	REMARK
⑥	PI film	—	1	Polyamide	Plating silvering	—
⑤	Terminal	—	4	Brass (0.30t)	ag Plated	—
④	Contact	—	1	F.ag/SUS	—	—
③	Base	—	1	LCP	Natural	—
②	Cover	—	1	Sus	Tin plated	—
①	Keystake	—	1	LCP	—	—

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
ΔX					ANGLAR ±5°
ΔX					L ≤ 4 ±0.2
ΔX					4 < L ≤ 16 ±0.3
					16 < L ≤ 63 ±0.4
					L > 63 ±0.5

REVISIONS
 www.alpsr.com www.gdxdz.com www.xbswitch.com

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWN	DATE	VIEW:	TACT SWITCH
CHKD	DATE	UNIT: mm	PART NO.: TS-1183SA-X-X
APPD	DATE	SIZE: A4	DWG NO.: TS-1183SA-X-X
DONG GUAN XI BANG ELECTRONIC CO., LTD			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0