


Code-x	H	Code-x	H
A	4.3	O	11.0
B	4.5	P	11.5
C	5.0	Q	12
D	5.5	R	12.5
E	6.0	S	13.0
F	6.5	T	13.5
G	7.0	U	14.0
H	7.5	V	15.0
I	8.0	W	15.5
J	8.5	X	16
K	9.0	Y	16.5
L	9.5	Z	17
M	10.0		
N	10.5		

**SPECIFICATION**

Contact rating: 50mA, 12V DC  
 Contact Resistance: 100m $\Omega$  max  
 Dielectric Strength: 250V AC/1minute  
 Travel: 0.25mm  
 Operating Temp: -30 $^{\circ}$ C ~ + 85 $^{\circ}$ C  
 Storage Temp: -30 $^{\circ}$ C ~ + 80 $^{\circ}$ C

PAPT NO	TC-1102DE-X-X
Operating Force	A:100gf B:160gf C:260gf
Height	Code-x



ITEM	PAPT NAMF	TER.NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	3	Brass (0.30t)	ag Plated		
④	Contact	1	F.ag/SUS			
③	Base	1	PPA			
②	Cover	1	Brass	Tin plated		
①	Keystake	1	PPA			

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
$\Delta$ X					units: mm
$\Delta$ X					tolerance: X.X $\pm 0.2$ mm
$\Delta$ X					X.XX $\pm 0.1$ mm
MARK					X.XXX $\pm 0.05$ mm

DSND	DATE	SCALE: N/A	MODEL TYPE: <b>TACT SWITCH</b>
DWN	DATE	VIEW:	PART NO.:
CHKD	DATE	UNIT: mm/in	DWG NO
APPD	DATE	SIZE: A4	<b>TC-1102DE-X-X</b>
DONG GUAN XI BANG ELECTRONIC CO., LTD			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0