



code-x	H
A	4.3
B	4.8
C	5.0
D	5.3
E	5.5
F	6.0

主要技术参数、性能
The Main Thchnology Performance
 额定电流、电压: 50mA DC12V
 Rate voltage,current: 50mA DC12V
 接触电阻: ≤100mΩ
 Contact resistance: ≤100mΩ
 按力: 50gf
 Operating force: 50gf
 行程: 0.20± 0.1 0mm
 Travel: 0.20± 0.1 0mm
 绝缘电阻: ≥100MΩ
 Insulated resistance: ≥100MΩ
 介电强度: ≥250VAC/1min
 Di electric strength: ≥250VAC/1min



电路图
 CIRCUIT DIAGRAM



PCB.焊接图
 PCB.WELDING DRAWING

PAPT NO	TC-1101DE-X-X
Operating Force	B:160gf C:260gf
Height	code-x

ITEM	PAPT NAMF	TER.NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	—	2	Brass (0.30t)	Plating silvering	—
④	Contact	—	1	F.ag/Sus	Natural	—
③	Base	—	1	PPA	—	—
②	Cover	—	1	Spcc	Plating Nickel	—
①	Keystake	—	1	PPA	—	—

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE: TACT SWITCH
ΔX					units: mm	DWN	DATE	VIEW:	PART NO.:
ΔX					tolerance:	CHKD	DATE	UNIT: mm/in	DWG NO
ΔX					X.X ±0.2mm	APPD	DATE	SIZE: A4	
ΔX					X.XX ±0.1mm	DONG GUAN XI BANG ELECTRONIC CO., LTD			
ΔX					X.XXX ±0.05mm				
REVISIONS						1.0g	1/1	A0	
www.alpsr.com www.gdxjdz.com www.xbswitch.com									