



NOTES:

- 1.0 RATING
- 1.1 TEMPERATURE: -25° c TO +75° c;
- 2.1 INSULATION RESISTANCE: 100M AT 500V DC
- 2.2 DIELECTRIC STRENGTH: AC 500V, 60Hz FOR 1MINUTE;
- 3.0 MATERIALS
- 3.1 HOUSING: THERMOPLASTIC;
- 3.2 CONTACT: COPPER ALLOY
- 4.0 INSERTION & EXTRACTION FORCE
- 4.1 INSERTION & EXTRACTION: 1.0 TO 2.5kgf;
AFTER LIFE TEST: 0.3 TO 2.5 kgf;



	MATERIAL	PLATING
terminal 1	Phosphor Bronze	tin
terminal 2	Phosphor Bronze	tin
terminal 3	Phosphor Bronze	tin
terminal 4	Phosphor Bronze	tin
terminal 5	Phosphor Bronze	tin
terminal 6	Phosphor Bronze	tin
plastic	Pbt	

MARK	DESCRIPTION	DATE	REVISED	APPROVED	ANGLAR	±5°	DSND	DATE	SCALE: N/A	MODEL TYPE:		
△X					X.X	±0.2mm	DWN	DATE	VIEW:	3.5 PHONE JACK		
△X					X.XX	±0.1mm	CHKD	DATE	UNIT: mm	PART NO.:		
△X					X.XXX	±0.05mm	APPD	DATE	SIZE: A4	DWG NO.:		
REVISIONS					UNSPECIFIED TOLERANCES		东莞市溪榜电子有限公司			WEIGHT	SHEET	REVISION
										1.0g	1/1	A0