



USS TYPE C 接线示意图

A4, A9, B9, B4	V
A5	
B5	
A1, A12, B1, B12	G
A6	D+
A7	D-
(R1=56KΩ R3=56KΩ) 5%	

- NOTES:
- MECHANICAL:
    - MATING FORCE: 5-20N
    - UNMATING FORCE: 8-20N
    - DURABILITY: 10000 CYCLES MIN.
  - ELECTRICAL:
    - CURRENT: 5.0A MAX
    - VOLTAGE: 20V MAX
    - WITHSTANDING VOLTAGE: 100V AC
    - CONTACT RESISTANCE: 40 mΩ MAX INITIAL;  
50 mΩ MAX AFTER 10000 CYCLES
  - ENVIRONMENTAL
    - OPERATING TEMPERATURE RANGE -30°C ~ +80°C

④	GND LATCH	1	STAINLESS STEEL	NICKEL PLATED OVERALL TAB WITH LEAD FREE TIN ALLOY.
③	CONTACT	16	COPPER ALLOY	NICKEL UNDERPLATING OVER ALL GOLD PLATING AT CONTACT AREA LEAD FREE TIN ALLOY AT TERMINATION.
②	SHELL	1	STAINLESS STEEL	CLEAN
①	HOUSING	2	THERMOPLASTIC UL 94V-0	MOLDED COLOR:BLACK white
NO.	DESCRIPTION	QTY.	MATERIAL	TREATMENT

## 东莞市溪榜电子有限公司

TOLERANCE:  UNIT: mm (inch) SCALE: 1:1 SIZE: A4	DRAWN BY:	DATE:	PART NAME: TYPE-C16P公头 立贴11.94	
	刘志强	2015.08.18	PART NO.	SEE TABLE
	CHECKED BY:	DATE:	MOLD NO.	
	李毅	2015.08.18	DRAW NO:	ZDJNKJ00001653
APPROVED BY:	DATE:	SHEET NO.	1 OF 1	
张少辉	2015.08.18			