







NOTES:

Housing: Thermoplastics, UL94V-0

Contact: Copper Alloy

Shell: Copper Alloy/Steel

Voltage Current Rating: 1.5 AMP. 30V AC

Insulation Resistance: 1000M Ω Min.Contact Resistance: 30 M Ω Max.

Dielectric Withstanding Voltage: 500V AC

Temperature Range: -35°C to +85°C

Insulator color: Black/White

Plastic material: PBT/LCP/Others

Shell finish: Nickel plated/Tin-Lead plated

Mechanical:

Mating Force: 3.5KG MAX

Unmating Force: 1.02 KG MIN.

Contact finish:

01: Selective Gold Flash

02: Selective Gold 3U"

03: Selective Gold 5U"

04: Selective Gold 15U"

05: Selective Gold 30U"

东莞市溪榜电子有限公司

DONG GUAN XIBANG ELECTRONICS CO., LTD.

TOLERANCE: X.X ±0.30 X.XX ±0.20 X.XXX ±0.10 X.° ±10° .X.° ±5° .X	DRAWN BY :	DATE : 2015.08.18	PART NAME: 侧插直边弯脚反向14.0	
	CHECKED BY :	DATE : 2015.08.18	PART NO.	SEE TABLE
	APPROVED BY :	DATE :	DRAW NO:	2015.08.18
	SCALE: 1:1	SIZE: A4	SHEET NO.	1 OF 1