



CHARACTERISTICS	
OPERATING FORCE (OF):	130gf Max.
RELEASE FORCE (RF):	15gf Min.
OPERATING POSITION:	6.75±0.2 mm.
PRE TRAVEL:	0.80mm Max.
DIFFERENTIAL TRAVEL:	0.20mm Max.
FREE POSITION:	7.40mm Max.

ELECTRICAL DATA	
RATING	OPERATING LIFE
3A 12VDC	100,000 CYCLES
0.1A 48VDC 125/250VAC	100,000 CYCLES
MECHANICAL LIFE	500,000 CYCLES
GAP TYPE	MICRO
OPERATING TEMP	-40°C ~ +85°C
WATERGROOF	IP67

OUTLINE DRAWING			
TITLE	H3 SERIES MICRO SWITCH		
MODEL	H3-B1		
PART NO.			
DRAFTED BY	BING WANG	DATE	2020-6-13
CHECKED BY	GUO FU LUO	DATE	2020-6-13
APPROVED BY	MATH	DATE	2020-6-13

Circuit Diagram		TOLERANCE UNLESS OTHERWISE SPECIFIED						
		1~3	3~10	10~30	30~100	100~200	ANGLE	
		±0.2	±0.3	±0.4	±0.6	±1.0	±1.5 ±3.0°	
		SCALE		UNIT		VERSION REV		
		mm		mm		A1		
溪榜电子有限公司								

1 2 3 4 5 6 7 8 9 10