

外形参数

OF Max:130gf

RF Min:15gf


PT Max:0.8mm

DT Max:0.2mm

FP Max:3.7mm

OP:3.05±0.2mm

Circuit Diagram



CHARACTERISTICS	
OPERATING FORCE(OF):	200gf Max.
RELEASE FORCE(RF):	50gf Min.
OPERATING POSITION:	8.40±0.30 mm.
FREE POSITION :	9.7 mm MAX
PRE TRAVEL:	1.3 mm Max.
DIFFERENTIAL TRAVEL:	0.20 mm Max.
OVER TRAVEL:	0.60 mm Min.

ELECTRICAL DATA	
<b>RATING</b>	<b>OPERATING LIFE</b>
5A 125/250VAC	10,000 CYCLES
<b>MECHANICAL LIFE</b>	<b>500,000 CYCLES</b>
<b>GAP TYPE</b>	<b>MICRO</b>
<b>OPERATING TEMP.</b>	<b>-40°C ~+105°C</b>
<b>WATERPROOF</b>	<b>IP67</b>

OUTLINE DRAWING			
TITLE	H5 SERIES MICRO SWITCH		
MODEL	H5-A1		
PART NO.			
DRAFTED BY	SHUANG WANG	DATE	2021-1-20
CHECKED BY	SHIGANG YOU	DATE	2021-1-20
APPROVED BY	MATH	DATE	2021-1-20

TOLERANCE UNLESS OTHERWISE SPECIFIED						
<3	3~10	10~30	30~100	100~200	ANGLE	
±0.2	±0.3	±0.4	±0.6	±1.0	±1.5	±3.0'
					SCALE	
					UNIT	mm
					VERSION	REV
						AO

溪榜电子有限公司