



Rating	3A 125VAC	Electrical Life	10,000 cycles
Contact Resistance	100mΩ Max	Mechanical Life	1,000,000 cycles
Insulation Resistance	>100MΩ DC500V	Ambient Temper. Used	-25°C to +85°C
Withstand Voltage	AC500V 1min.	Ambient Humidity Used	≤85% at +40°C
Soldering Temper.	235±5°C 5s	Operating Force	30±15gf

9	Wheel	1	PBT	
8	Axle	1	C2600	
7	Lever	1	SUS	
6	Terminal	3	C2600	Ag-plating
5	Contact	3	AgNi10	
4	Button	1	PBT	
3	Spring	1	C17200	
2	House	1	PBT	
1	Base	1	PBT	
No.	Name	Number	Material	Remark

东莞市溪榜电子有限公司

制图		比例	4:1	名称	微动开关	
设计		数量	1/1	料号		
审核		单位	mm	模具编号		
批准		公差	±0.10	角度	±1.0°	
一般公差		公差	±0.15	公差	±0.02	
TOLERANCE		公差	±0.10	公差	±0.02	
		公差	±0.05	公差	±0.02	

版本	变更内容	日期	修改	批准
REV.	CHG. NO.	DATE	DRW.	APPROVE