



序号	名称	材质	数量
1	圆针插销	黄铜棒	2
2	基座	PA66	1
3	保险管	PA66	1
4	快接端子	黄铜t0.8	1
5	快接端子	黄铜t0.8	1
6	保险夹	磷铜t0.5	2
7	连接片	黄铜t0.5	1
8	铆钉	黄铜t2.0	2

Rating :

2.5A 250V AC TUV 3C KC CE

Fuse : 250V 6.3A 2.5W

Insert And Extract Force: 1.36kgf~6.8kgf

Terminal Strength: ≥80N

Operating Life: ≥5000 cycles

Withstand Voltage: Between all terminals: 2500VAC (50-60Hz) 1min

terminals to Base: 3750V AC (50-60Hz) 1min

Leakage Current : 1mA

Insulation Resistance: ≥100MΩ 500V DC

A4				普通公差	东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD Switch Connector								
A3				COMMON TOLERANCE :									
A2				UP TO 5	±0.20	单位	mm	投影	⊕	品名	Ac Inlet C8型	比例	Free
A1				ABOVE 5 TO 30	±0.30	UNIT		PROJECTED	⊕	PRODUCT NAME		SCALE	
REV.	DATE	REVISION DESCRIPTION	ISSUE	ABOVE 30	±0.50	绘图		核 对		料 号			
				ANGULAR	±5°	日期		核 准		图 号			
						DATE		APPROVAL BY		图 号			
										XB-AC-8-F5LZ			
										图 号			
										FIG. NO.			