



SECTION A-A

序号	名称	材质	数量
1	基座	环阻尼龙 94V-0	1
2	圆针插销	H65 黄铜棒	2
3	焊线端子	H62 Copper t0.8	2

Rating :

2.5A 250V AC

Insert And Extract Force: 1.36kgf~6.8kgf

Terminal Strength: $\geq 80N$

Operating Life: ≥ 5000 cycles

Withstand Voltage: Between all terminals:2500VAC (50-60Hz)1min

terminals to Base:3750V AC (50-60Hz)1min

Leakage Current : 1mA

Insulation Resistance: $\geq 100M\Omega$ 500V DC

A4				普通公差		 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD Switch Connector							
A3				COMMON TOLERANCE :									
A2				UP TO 5	± 0.20	单位	mm	投影		品名	Ac Inlet C8型	比例	Free
A1				ABOVE 5 TO 30	± 0.30	UNIT		PROTECTED		PRODUCT NAME		SCALE	
REV.	DATE	REVISION DESCRIPTION	ISSUE	ABOVE 30	± 0.50	绘图	高鹏	核对	贺龙飞	料号	XB-AC-8-42LZ		
				ANGULAR	$\pm 5^\circ$	日期	2024-8-1	核准	庞东	图号			