



| 序号 | 名称   | 材质              | 数量 |
|----|------|-----------------|----|
| 1  | 圆针插销 | H65 黄铜棒         | 2  |
| 2  | 基座   | 环阻尼龙 94V-0      | 1  |
| 3  | 焊线端子 | H62 Copper t0.8 | 2  |

Rating :

2.5A 250V AC 3C KC TUV CE  
7A 125V AC UL cUL

Insert And Extract Force: 1.36kgf-6.8kgf

Operating Life: ≥5000 cycles

Withstand Voltage: Between all terminals:2500VAC (50-60Hz)1min  
terminals to Base:3750V AC (50-60Hz)1min  
Leakage Current : 1mA

Insulation Resistance: ≥100MΩ 500V DC

|      |      |          |             |                    |         |  |      |           |     |              |              |               |      |
|------|------|----------|-------------|--------------------|---------|--|------|-----------|-----|--------------|--------------|---------------|------|
| A4   |      |          |             | 普通公差               |         |  <b>东莞市溪榜电子有限公司</b><br>DONG GUAN XI BANG ELECTRONICS CO., LTD |      |           |     |              |              |               |      |
| A3   |      |          |             | COMMON TOLERANCE : |         |  |      |           |     |              |              |               |      |
| A2   |      |          |             | UP TO 5            | ±0.20   | 单位   | mm   | 投影        | ⊕   | 品名           | Ac Inlet C8型 | 比例            | Free |
| A1   |      |          |             | ABOVE 5 TO 30      | ±0.30   | UNIT   |      | PROJECTED |     | PRODUCT NAME |              | SCALE         |      |
| REV. | DATE | REVISION | DESCRIPTION | ISSUE              | ANGULAR | ±5°  | 日期   | 2024-8-1  | 核 对 | 贺龙飞          | 料 号          | XB-AC-8-6S9LZ |      |
|      |      |          |             |                    |         |  | DATE |           | 核 准 | 庞东           | 图 号          |               |      |