



序号	名称	材质	数量
1	底座	PA66	1
2	接地插销	黄铜t2.0	1
3	载流插销	黄铜t2.0	2
4	接触弹片	黄铜t0.4	2
5	保险盖	PA66	1
6	保险夹	磷铜t0.4	2
7	铆钉	黄铜t2.0	2
8	快插端子	黄铜t0.8	3

Rating :

10A 250V AC T105 UL cUL
TUV 3C KC CE

FUSE: 250V max 1.6W

Insert And Extract Force: 1.36kgf~6.8kgf

Terminal Strength: ≥80N

Operating Life: ≥5000 cycles

Withstand Voltage: Between all terminals:2500VAC (50-60Hz)1min
terminals to Base:3750V AC (50-60Hz)1min
Leakage Current : 1mA

Insulation Resistance: ≥100MΩ 500V DC

A4				普通公差		 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD Switch Connector							
A3				COMMON TOLERANCE :									
A2				UP TO 5	±0.20	单位	mm	投影	第一角	品名	Ac Inlet C14型	比例	Free
A1				ABOVE 5 TO 30	±0.30	绘图	吴瑜	核对		料号	XB-AC-14-F7B	SCALE	
				ABOVE 30	±0.50	日期	2020. 12. 7	核准		图号			
REV.	DATE	REVISION	DESCRIPTION	ISSUE	ANGULAR	±5°	DATE	APPROVAL BY		DWG. NO.			