



NOTES:

- Rating:
 - VDE ENEC 16(4)A 250V AC T85/55
 - KC 16(4)A 250V AC T85/55
 - CQC 16(4)A 250V AC T105/55
 - UL cUL 16GPA 125V AC/16GPA 250V AC T105/55
- Circuit Diagram: 4P ON-OFF
- Terminal Strength: $\geq 80N$
- Electrical life: ≥ 10000 cycles
- Withstand Voltage: Withstand Voltage: 1500VAC 1min
Terminals to Button: 3000VAC 1min
Leakage Current: 1mA
- Current resistance: $\leq 50m\Omega$ (initial)
- Insulation resistance: $\geq 100M\Omega$
- Body Materil: NYLON 66 94V-0[~]2

PANEL CUT-OUT		
Z	Y	X
0.80~1.25	25.10~25.30	33.1~33.3
1.25~2.00	25.10~25.30	33.3~33.6
2.00~3.00	25.10~25.30	33.6~33.8

9	基座	1	环保阻燃PA66		
8	弯端	2	0.8mm黄铜带 +复合银触点	镀锡	
7	中端	2	0.8mm黄铜带	镀锡	
6	接触桥	2	0.8mm黄铜带 +复合银触点	镀银	
5	套管	2	0.3mm拉伸钢	镀镍	
4	弹簧	2	$\varnothing 0.40$ 弹簧钢丝	发黑	
3	氖灯	1			绿灯
2	内套	1	环保阻燃PA66		
1	带灯按钮	1	环保阻燃PC		
序号	名称	数量	材料	处理	备注

A4				普通公差:		东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD Switch Connector							
A3				COMMON TOLERANCE :									
A2				UP TO 5	± 0.20	单位	mm	投影		品名	跷板开关	比例	Free
A1				ABOVE 5 TO 30	± 0.30	绘图	GAO. PENG	核对	PANG. DONG	型号	XB-RS-606FD1		
REV.	DATE	REVISION DESCRIPTION	ISSUE	ANGULAR	$\pm 5^\circ$	日期	2024.3.8	核准	HE. LONG. FEI	图号	XB Rocker switch		