



适用FPC寸法
APPLICABLE FPC

No. of PINS/ROW	Dimension Information		
M	L1	L	
06	5.00	8.10	9.20
08	7.00	10.10	11.20
10	9.00	12.10	13.20
12	11.00	14.10	15.20

Specifications
 Current Rating:1.0Amp
 Operating Voltage:50V AC/DC
 Insulation Resistance:100MΩMin.
 Dielectric Withstanding Voltage:500VAC
 Contact Resistance:0.03mΩMax.
 Operating Temperature:-40°C to +85°C
 Materials
 Contact Material:Phosphor Bronze
 Insulator Material: UL 94V-0 LCP
 All materials must meet XI BANG hazardous substances control standards.

Ordering Information

XB-FPC-10-104-A008-XX-XX

A 008 C X A X

No. of Pins Per Row
06.08.10.12

Standard Plating
XX

Color
2=White

Standard Packing
D=T&R

东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD

3RD.ANG PROJ.
PAGE. 1/1

GENERAL TOLERANCE	
X.*±5.0°	X.±0.30
.X*±3.0°	.X±0.25
.XX*±2.0°	.XX±0.15
.XXX*±1.0°	.XXX±0.10

DESIGNED:
CHECKED:
APPROVED:

DATE:
DATE:
DATE:

DWG. NO.
XB-FPC-10-104-A008
PART NO.

TITLE.
1.0 FPC CONN NON-ZIF SMT
H=5.40 VERTICAL CONTACT

REV. A UNIT. mm SCALE. 1:1