



Recommended P.C.B Layout(Top Side)
(Tolerance=±0.05)

Specifications
 Current Rating: 1Amp
 Insulation Resistance: 1000MΩ Min.
 Dielectric Withstanding Voltage: 500V AC
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -25°C to +85°C

Materials
 Contact Material: Brass.
 Insulator Material: Thermoplastic, UL 94V-0
 Nylon 66 or the equivalent material
 All materials must meet XI BANG
 requirement for environment protection

Ordering Information

XB-X20-PCB-103 XX XX **A** **804** **E** X **B** X

No. of Pins per Row 02~16 Standard Plating 02=Gold Flash
 Selective Plating 01=Tin 05=Gold Flash/Tin

Color 1=Black 2=White Standard Packing B=Tray
 Selective Packing C=Tube

No. of PIN/ROW	Dimension Information	
	M	L
02	2.00	6.00
03	4.00	8.00
04	6.00	10.00
05	8.00	12.00
06	10.00	14.00
07	12.00	16.00
08	14.00	18.00
09	16.00	20.00
10	18.00	22.00
11	20.00	24.00
12	22.00	26.00
13	24.00	28.00
14	26.00	30.00
15	28.00	32.00
16	30.00	34.00

东莞市溪榜电子有限公司
 DONG GUAN XI BANG ELECTRONICS CO., LTD

GENERAL TOLERANCE	
X: ±5.0'	X: ±0.30
.X: ±3.0'	.X: ±0.25
.XX: ±2.0'	.XX: ±0.15
.XXX: ±1.0'	.XXX: ±0.10

DESIGN:	DATE:
CHECKED:	DATE:
AUDITED:	DATE:

DWG. NO.	DATE:
XB-X20-PCB-103	DATE:
PART NO.	DATE:

TITLE.
2.00mm 90° WAFER

REV. 01	UNIT. mm	SCALE. 1:1	PAGE. 1/1	
---------	----------	------------	-----------	--